



PRODUCT DESCRIPTION:

BDI EVERBLOCK is a revolutionary new product designed to seal and protect a variety of dense and porous natural stone, clay and masonry surfaces. *EVERBLOCK* produces an invisible, protective barrier that helps repel cooking oils, grease, water, beverages, food and animal soiling, while leaving the surface unchanged in appearance. *EVERBLOCK* is water based and contains no harsh solvents or fumes, making it both safe and ideal for use by do-it-yourselfers and professionals. *EVERBLOCK* is excellent for use in food service areas, patient care facilities or wherever the use of solvents is restricted or prohibited. *EVERBLOCK* is a breathable treatment, while still imparting a high degree of water repellency on the treated surface.

RECOMMENDED FOR USE ON:

A variety of highly porous, dense, textured, flamed and tumbled natural stone surfaces such as granite, slate, unfinished marble, quarry tile, brick, cantera, adoquin, flagstone, limestone, saltillo clay tiles, terracotta, cement tiles, concrete, sanded grout and unpainted wood. *EVERBLOCK* is recommended for use on interior, exterior, residential and commercial applications. *EVERBLOCK* is perfect for showers, countertops, bathrooms, kitchens, clay pots, fountains and ornamental stone. Although this product is suitable for tumbled, unfinished and similar textured surfaces, it is *not* recommended for use on highly polished marble, metal, glass, plastic or similar impervious surfaces.

SURFACE PREPARATION:

All surfaces must be clean, dry and porous, free from all loose debris, dirt, dust, grease, silicones, waxes, oils, cleaners, grout releases and foreign material. Clean area with a solution of *EVERCLEAN* and water. For heavy soiling use *EVERCLEAN 2000*. Allow area to thoroughly dry before applying sealer.

DIRECTIONS FOR USE: Always test this product first in a small area on the surface to which it is to be applied before approving for your intended use,

or attempting the entire sealing procedure. Some surfaces may experience slight colour enhancement. *EVERBLOCK* can be applied by brush, sponge, lambswool applicator, 1/4 to 1/2 inch nap paint roller, foam roller, clean white absorbent cloth or low pressure hand pump spray equipment. Apply sealer slowly, in a uniform and even manner leaving no puddles or voids.

FOR POROUS SURFACES: Apply sealer liberally. Allow sealer to completely absorb into the surface and re-apply sealer to the same area within 20 minutes. Additional coats can be applied to increase protection on highly porous surfaces. Allow sealer to cure overnight before subjecting area to normal use.

FOR DENSE SURFACES: Apply sparingly. Any material not readily absorbed within 1 to 2 minutes should be removed by buffing until dry with a clean absorbent cloth. Allow sealer to cure overnight before subjecting to normal use.

FOR USE AS A GROUT RELEASE: Apply and allow to dry overnight before attempting the grout procedure. Always test for proper grout release. If grout does not release successfully or staining is evident, clean the surface, allow to dry and apply another coat of *EVERBLOCK*.

Allow sealer to thoroughly dry and re-attempt the grout release test until successful. If acid is used to clean area or remove grout smears, haze or residue, neutralize area afterwards with a solution of *EVERCLEAN* and water. Allow area to dry completely and apply sealer as directed.

FOR SEALING EXISTING GROUT: Recommended for use on porous, sanded, unsanded, quarry grade and cement grout mixtures. Not recommended for epoxy grout, grouts sealed with gloss type sealers or other similar impervious surfaces.

Thoroughly clean grout with *EVERGROUT* using a stiff bristle brush. Rinse with a solution of clean water and *EVERCLEAN* and allow grout to completely dry. Seal grout joints with *EVERBLOCK* using the Ever Applicator bottle designed for grout use.

Water based
No Fumes
Non-Toxic
Easy to Use
Natural Look
Matt Finish

Do not allow sealer to dry on the surface of the tile. Wipe off any excess by buffing until dry with a clean absorbent cloth.

WHEN A GLOSS IS DESIRED: After applying *EVERBLOCK*, apply *EVERPOLISH* until desired level of gloss is achieved. Some surfaces may exhibit an extremely high degree of repellency after being treated with *EVERBLOCK* and may initially reject the floor polish. This can be overcome by lightly abrading the surface with a medium abrasive scrubbing pad before applying the polish. Remove all loose debris before applying polish.

MAINTENANCE:

Sweep, dust mop or wipe with a clean cloth often. Wipe up spills as soon as possible with a clean absorbent cloth. Clean with a mild solution of *EVERCLEAN* and water.

COVERAGE IN SQ. FEET PER LITRE:

Highly Porous Surfaces: 18-135.
Dense Surfaces: 165-500.

PACKAGE SIZE:

1 litre, 2.5 litre, 5 litre, 19 litre
 113 litre drum.

SPECIAL PRECAUTIONS:

Do not aerosolize or atomize under high pressure. As with any chemical compound, read and understand the Material Safety Data Sheet (MSDS) before initial use. Keep away from children. Keep this product from freezing.

TECHNICAL PROFILE:

Viscosity:	Water Thin
Solvent:	Water
Active Solids:	8.5%
pH:	6.5
Shipping Category:	Non Hazardous